

NAVASTRID

Absperrentechnik

www.navastrid.de



Page - 04
Barrier Post



Page - 22
Work Site
Protection




Page - 40
BiCycle Rack



Page - 50
Barrier Gate





Eyelets

Inside Ø 20 mm
Outside Ø 35 mm

For round and square
tube barriers



Triangular Lock

according to DIN 3223


For round and square
tube barriers



Profile cylinder lock

with 3 keys
German branded product


For round and square tube
barriers



Bottom Plate

can be screwed onto a
ground socket

Hole spacing: 70 x 122 mm



Hinged Bottom Plate


fixed with post and for
titling



The Barrier posts are always hot-dip galvanized according to DIN EN ISO 1461. Bollards are made of high-quality aluminum or hot-dip galvanized steel.


Color Code - The information is non-binding with regard to color and brilliance. It is for the purpose of giving you an impression of the coatings we supply.

We reserve the right to make changes in design, appearance and function. Dimensions are approximate dimensions. No liability is assumed for any printing errors.



1. Barrier posts

This barrier or chain post can be used as a boundary post for pedestrian street, parking lot, road, security zone, etc. The barrier with the stable locking and easy handling guarantees a quick opening of the blockade



Barrier post Ø 60x 2.6 mm

Many variety with above ground 900 mm

Article.

- Stationary post for casting in concrete (with 2 eyelets)
- Stationary post to be fixed by plugs (with 2 eyelets)
- Removable post with Triangle lock and included ground socket (with 2 eyelets)
- Removable post with Euro profile cylinder lock and included ground socket (with 2 eyelets)
- Removable post for padlock and included ground socket (with 2 eyelets)
- Foldable post with Triangle lock
- Foldable post with Euro Profile cylinder lock
- Foldable post for padlock

Article no.

- 44-60-Typ1
- 44-60-Typ2
- 44-60-Typ3
- 44-60-Typ4
- 44-60-Typ8
- 44-60-Typ6
- 44-60-Typ5
- 44-60-Typ9

Weight.

- 5.4 kg
- 5.4 kg
- 7.5 kg
- 6.8 kg
- 7.4 kg
- 5.8 kg
- 5.9 kg
- 6.9 kg

Price (DAP)

- € 18.10
- € 16.50
- € 38.50
- € 49.80
- € 27.10
- € 30.10
- € 43.50
- € 35.80



The Barrier Post - Steel tube Ø 60 x 2.6 mm with welded steel cap and 900 mm above ground, are Hot Dip Galvanized and white coated with three 3M reflective stripes (color - RAL300). The triangular locking mechanism made acc. with DIN 3223, self-engaging lock.


The foldable post with Euro profile lock, Triangular lock and Padlock, either fixed by plugs or with ground socket article no: 541-A6, available separately, Refer Page 19

Note: Order also accepted with only Hot Dip Galvanizing



Eyelets

inner diameter Ø20mm
outer diameter Ø35mm



Barrier post Ø 76 x 2.6 mm
Many variety with above ground 900 mm

Article.

- Stationary post for casting in concrete (with 2 eyelets)
- Stationary post to be fixed by plugs (with 2 eyelets)
- Removable post with Triangle lock and included ground socket (with 2 eyelets)
- Removable post with Euro profile cylinder lock and included ground socket (with 2 eyelets)
- Foldable post with Triangle lock
- Foldable post with Euro profile cylinder lock

Article no.	Weight.	Price (DAP)
44-76-Typ1	6.6 kg	€ 20.10
44-76-Typ2	5.3 kg	€ 17.80
44-76-Typ3	10.7 kg	€ 46.00
44-76-Typ4	11.1 kg	€ 65.30
44-76-Typ5	7.0 kg	€ 36.30
44-76-Typ6	8.4 kg	€ 61.50




The Barrier Post - Steel tube Ø76x 2.6 mm with welded steel cap 900 mm above ground. The foldable post with Euro profile lock and Triangular lock either fixed by plugs or with ground socket article no: 541-A6, available separately, Refer Page 19.

Note: Order also accepted with only Hot Dip Galvanizing

Also available in yellow/black,
see work site protection pages 129 ff



Barrier Post - Steel tube Ø 101



44-101-Typ1



44-101-Typ2



44-101-Typ3

Steel tube bollards Ø 101 x 3 mm

Stationary for casting in concrete

Steel tube bollards Ø 101 x 3 mm

for temporary removable including ground socket

Article.

Stationary post for casting in concrete

Stationary post to be fixed by plugs

Removable post with Triangle lock and included ground socket

Article no.

44-101-Typ1

44-101-Typ2

44-101-Typ3

Weight.

9.8 kg

9.9 kg

14.5 kg

Price (DAP)

€ 33.50

€ 33.80

€ 63.40



The Barrier Post - Steel tube Ø 101 x 3 mm with welded steel cap and 900 mm above ground, are Hot Dip Galvanized and white coated with three 3M reflective stripes (color - RAL300). The triangular locking mechanism made acc. with DIN 3223, self-engaging lock.

Note: Order also accepted with only Hot Dip Galvanizing



Steel tube bollards Ø 152 x 3.6 mm

Stationary for casting in concrete

Steel tube bollards Ø 152 x 3.6 mm

for temporary removable including ground socket

Article.

Stationary bollards for casting in concrete, Length 1200mm
 Stationary bollards for casting in concrete, Length 1500mm
 Stationary bollards for casting in concrete, Length 2000mm
 Stationary bollards to be fixed by plugs, Length 1000mm
 Removable bollards without lock and included ground socket, Length 1500mm
 Removable bollards without lock and included ground socket, Length 2000mm
 Removable bollards with Triangular lock and included ground socket, Length 1000mm

Article no.	Weight.	Price (DAP)
44-152-Typ1A	17.6 kg	€ 54,10
44-152-Typ1B	21.8kg	€ 67,50
44-152-Typ1C	28.8 kg	€ 89,00
44-152-Typ2	17.7 kg	€ 60,00
44-152-Typ3A	32.8 kg	€ 130,00
44-152-Typ3B	39.8 kg	€ 156,00
44-152-Typ4	21.7kg	€ 93,00



Note: Order also accepted with only Hot Dip Galvanizing

Also available in yellow/black,
see work site protection pages 129 ff





44-193-Typ1-B



44-193-Typ2



44-193-Typ3-A



44-193-Typ4

Steel tube bollards Ø 193 x 3.6 mm

Stationary for casting in concrete

Steel tube bollards Ø 193 x 3.6 mm

for temporary removable including ground socket

Article.

Stationary bollards for casting in concrete, Length 1200mm

Stationary bollards for casting in concrete, Length 1500mm

Stationary bollards for casting in concrete, Length 2000mm

Stationary bollards to be fixed by plugs, Length 1000mm

Removable bollards without lock and included ground socket, Length 1500mm

Removable bollards without lock and included ground socket, Length 2000mm

Removable bollards with Triangular lock and included ground socket, Length 1000mm

Article no.

44-193-Typ1-A

44-193-Typ1-B

44-193-Typ1-C

44-193-Typ2

44-193-Typ3-A

44-193-Typ3-B

44-193-Typ4

Weight.

22.5 kg

27.9 kg

36.8 kg

27.1 kg

27.6 kg

51.0 kg

25.7 kg

Price (DAP)

€ 77,60

€ 96,00

€ 126,50

€ 101,00

€ 180,50

€ 218,00

€ 160,00



These post are Hot Dip Galvanized and white coated with three reflective three 3M reflective stripes (color - RAL300). The triangular locking mechanism made acc. with DIN 3223, self-engaging lock.


Note: Order also accepted with only Hot Dip Galvanizing



These heavy bollards can be used as collision protection, especially in front of entrances, halls, petrol stations, etc. They can also protect roof overhangs or serve as a guide Bollards in front of ramps, gates etc.

Steel tube bollards Ø 273 x 5.0 mm

Stationary, for casting in concrete with welded steel cap




Article.

Stationary bollards for casting in concrete, Length 1500mm

Stationary bollards for casting in concrete, Length 2000mm

Stationary bollards to be fixed by plugs, Length 1500mm

Article no.	Weight.	Price (DAP)
44-273-Typ1-A	51.3 kg	€ 188,00
44-273-Typ1-B	67.8 kg	€ 249,00
44-273-Typ2	59.0 kg	€ 234,00



HDG Bollards



Stickered Bollards




Packed Bollards

Barrier Post - Steel tube 70 x 70 (Unfoldable)



These barrier posts can be opened both with a Euro profile cylinder key and a triangular wrench that conforms with DIN 3232. This ensures that the fire brigade and rescue services have access at any time.



Barrier post 70 x 70 x 2.6 mm

removable with key and 900mm above ground

Article.

- Stationary post for casting in concrete
- Stationary post to be fixed by plugs
- Removable post with Triangle lock and included ground socket
- Removable post with Euro profile cylinder lock and included ground socket
- Removable post with **Combo** "Triangle & Euro profile cylinder lock "and included ground socket

Article no.

- 55-70-Typ1
- 55-70-Typ2
- 55-70-Typ5
- 55-70-Typ4
- 55-70-Typ7





Weight. Price (DAP)

- 7.7 kg € 24,60
- 6.9 kg € 24,60
- 15.5 kg € 47,00
- 14.3 kg € 53,00
- 14.2 kg € 59,00



These stationary and removable Post are Hot Dip Galvanized and white coated with three 3M reflective stripes (color - RAL300). The triangular locking mechanism made acc. with DIN 3223, self-engaging lock.

Note: Order also accepted with only Hot Dip Galvanizing and Option for post with eyelets too available



Barrier post 70 x 70 x 2.6 mm
foldable with key and 900mm above ground




- Article.**
- Foldable post with Triangle lock
 - Foldable post with Euro profile cylinder lock
 - Foldable post with hook (option to lock with padlock)
 - Foldable post with **Combo** "Triangle & Euro profile cylinder lock "
 - Foldable & Removable post with **Combo** "Triangle & cylinder lock "and incl ground socket

Article no.	Weight.	Price (DAP)
55-70-Typ6	8.7 kg	€ 53,00
55-70-Typ3	8.7 kg	€ 49,00
55-70-Typ10	8.1 kg	€ 59,00
55-70-Typ8	7.6 kg	€ 64,00
55-70-Typ9	13.4 kg	€ 59,00



The Barrier Post - Steel tube 70 x 70 mm with welded steel cap 900 mm above ground, are foldable post with Euro profile lock and Triangular lock either fixed by plugs or with ground socket article no: 541-A6, available separately, Refer Page 19.

Note: Order also accepted with only Hot Dip Galvanizing and Option for post with eyelets too available



Barrier post 70 x 70 x 2.6 mm

Foldable, with locking with lifting and tilting mechanism,



Barrier post 70 x 70 x 2.6 mm

Fully retractable with locking system

Article.

- Foldable post with Triangle lock
- Foldable post with Euro profile cylinder lock
- Retractable post with Triangle lock
- Retractable post with Euro profile cylinder lock

Article no.

- 55-70-Typ11
- 55-70-Typ12
- 55-70-Typ13
- 55-70-Typ14

Weight.


- 12.6 kg
- 12.1 kg
- 16.8 kg
- 17.1 kg

Price (DAP)

- € 53,00
- € 73,00
- € 93,00
- € 97,00




Note: Order also accepted with only Hot Dip Galvanizing



with 8mm
triangular lock



8mm key
Article no N575



Barrier post 70 x 70 x 2.6 mm - With 8 mm triangular locking alternative to the conventional triangular lock

Barrier post 70 x 70 x 2.6 mm - This 500 mm high post is very suitable for parking situation without enough space

Article.

- Removable post with 8mm Triangle lock and included ground socket
- Fordable post with 8mm Triangle lock
- Foldable post with Triangle lock, above ground 500mm
- Foldable post with Euro profile cylinder lock, above ground 500mm

Article no.

- 55-70-Typ15
- 55-70-Typ16
- 55-70-Typ17
- 55-70-Typ18

Weight.

- 12.00 kg
- 7.6 kg
- 15.4 kg
- 6.0 kg


Price (DAP)

- € 76,00
- € 54,00
- € 40,00
- € 45,00



These post are Hot Dip Galvanized and coated with 3M reflective stripes (color - RAL300). The triangular locking mechanism made acc. with DIN 3223, self-engaging lock. the foldable post with Euro profile lock and Triangular lock either fixed by plugs or with ground socket article no: 541-A6, available separately, Refer Page 19.

Note: Order also accepted with only Hot Dip Galvanizing



Passage and car-park barriers

Square tube 70 x 70 mm with lateral round tube hoops with width approx. 800 mm and above ground 500 mm

Passage and car-park barriers

Square tube 70 x 70 mm with lateral round tube hoops with width approx. 800 mm and above ground 900 mm

Article.

- Foldable Car park barrier with triangular locking (above ground 500 mm)
- Foldable Car park barrier with Euro profile cylinder lock (above ground 500 mm)
- Foldable Car park barrier with triangular locking (above ground 900 mm)
- Foldable Car park barrier with Euro profile cylinder lock (above ground 900 mm)
- Removable Car park barrier with Triangle lock and included ground socket
- Removable Car park barrier with Euro profile cylinder lock and included ground socket

Article no.

Article no.	Weight.	Price (DAP)
61-70-Typ3	7.8 kg	€ 20.10
61-70-Typ4	9.1 kg	€ 17.80
60-70-Typ3S	10.7 kg	€ 46.00
61-70-Typ2	12.0 kg	€ 65.30
60-70-Typ5S	7.0 kg	€ 36.30
61-70-Typ1	22.0 kg	€ 61.50



The Car park barrier - Steel tube 70 x 70 mm with welded steel cap 900 mm above ground, are foldable post with Euro profile lock and Triangular lock either fixed by plugs or with ground socket article no: 541-A6, available separately, Refer Page 19.

Note: Order also accepted with only Hot Dip Galvanizing



Passage and car-park barriers

Square tube 70 x 70 mm with lateral round tube hoops with width approx. 800 mm and above ground 500 mm

Passage and car-park barriers

Square tube 70 x 70 mm with lateral round tube hoops with width approx. 800 mm and above ground 900 mm

Article.

- Foldable Car park barrier with Euro profile cylinder lock (above ground 500 mm)
- For casting in concrete Car park barrier with Euro profile cylinder lock (above ground 500 mm)
- Foldable Car park barrier with 8mm triangle lock (above ground 500 mm)
- For casting in concrete Car park barrier with 8mm triangle lock (above ground 500 mm)

Article no.

- 61-70-Typ1
- 61-70-Typ2
- 61-70-Typ3
- 61-70-Typ4

Weight.

- 9.1 kg
- 7.6 kg
- 9.1 kg
- 7.6 kg


Price (DAP)

- € 20.10
- € 17.80
- € 46.00
- € 65.30



The Barrier Post - Steel tube 70 x 70 mm with welded steel cap 900 mm above ground, are foldable post with Euro profile lock and Triangular lock, either fixed by plugs or with ground socket article no: 541-A6, available separately, Refer Page 1976.

Note: Order also accepted with only Hot Dip Galvanizing and Option for post with eyelets too available

**Article.**

- Foldable Car park barrier with triangular locking (above ground 500 mm)
- Foldable Car park barrier with Euro profile cylinder lock (above ground 500 mm)
- Foldable Car park barrier with triangular locking (above ground 900 mm)
- Foldable Car park barrier with Euro profile cylinder lock (above ground 900 mm)
- Removable Car park barrier with Triangle lock and included ground socket
- Removable Car park barrier with Euro profile cylinder lock and included ground socket

Article no.

- 44-76-Typ1
- 44-76-Typ2
- 44-76-Typ3
- 44-76-Typ4
- 44-76-Typ5
- 44-76-Typ6

Weight. Price (DAP)

- 6.6 kg € 20.10
- 5.3 kg € 17.80
- 10.7 kg € 46.00
- 11.1 kg € 65.30
- 7.0 kg € 36.30
- 8.4 kg € 61.50



The Car park barrier - Steel tube 70 x 70 mm with welded steel cap 900 mm above ground, are foldable post with Euro profile lock and Triangular lock either fixed by plugs or with ground socket article no: 541-A6, available separately, Refer Page 1976.

Note: Order also accepted with only Hot Dip Galvanizing



Car park barrier

Made of thick-walled round steel tube Ø 33.7 x 2.5 mm
height approx. 450 mm, width approx. 850 mm, extremely flat
when folded down, approx. 45 mm high



61-70-Typ12



61-70-Typ13



61-70-Typ14

Article.

- Foldable Car park barrier with triangular locking (above ground 500 mm)
- Foldable Car park barrier with Euro profile cylinder lock (above ground 500 mm)
- Foldable Car park barrier with triangular locking (above ground 900 mm)
- Foldable Car park barrier with Euro profile cylinder lock (above ground 900 mm)
- Removable Car park barrier with Triangle lock and included ground socket
- Removable Car park barrier with Euro profile cylinder lock and included ground socket

Article no.

- 44-76-Typ1
- 44-76-Typ2
- 44-76-Typ3
- 44-76-Typ4
- 44-76-Typ5
- 44-76-Typ6

Weight.

- 6.6 kg
- 5.3 kg
- 10.7 kg
- 11.1 kg
- 7.0 kg
- 8.4 kg

Price (DAP)

- € 20.10
- € 17.80
- € 46.00
- € 65.30
- € 36.30
- € 61.50



The Car park barrier - Steel tube 70 x 70 mm with welded steel cap 900 mm above ground, are foldable post with Euro profile lock and Triangular lock either fixed by plugs or with ground socket article no: 541-A6, available separately, Refer Page 1976.

Note: Order also accepted with only Hot Dip Galvanizing



Multipurpose wrench, Triangular Key for posts and barriers

Article no. N570 - Grey cast multipurpose wrench made acc. with DIN 3223, for all barrier posts with triangular locking mechanism and for opening the covers

Article no. N571 - Triangle wrench made acc. with DIN 3223, for all barrier posts with triangular lock

Article.	Article no.	Weight.	Price (DAP)
Multipurpose wrench	N570	0.4 kg	€ 3,90
Triangular wrench	N571	0.2 kg	€ 2,90
Square socket wrench (6mm)	N573	0.2 kg	€ 2,00
Triangular wrench (8mm)	N575	0.1 kg	€ 2,20



Ground sockets and cover for Barrier Post - Steel tube Ø 60

Article.	Article no.	Weight.	Price (DAP)
Ground socket for Barrier post Ø 60 mm without locking mechanism	541-A3	2.1 kg	€ 7,70
Ground socket for Barrier post Ø 60 mm with locking mechanism	541-A4	2.1 kg	€ 7,70
Ground socket for Barrier post Ø 60 mm locking mechanism for pad lock	541-A5	2.3 kg	€ 8,40
Ground socket with mounted plate 100 x 150 (for folding barrier)	541-A6	3.0 kg	€ 11,00
Cover for Ø 60 ground socket without locking mechanism	N561	0.7 kg	€ 2,60
Cover for Ø 60 ground socket with locking mechanism (open by Multipurpose wrench)	N562	1.0 kg	€ 3,70



Ground sockets and cover for Barrier Post - Steel tube Ø 60 mm & Sq 70 x 70 mm

Article.	Article no.	Weight.	Price (DAP)
Ground socket for Barrier post Ø 76 mm without locking mechanism	541-A8	3.3 kg	€ 12,10
Ground socket for Barrier post Ø 76 mm with locking mechanism	541-A9	3.3 kg	€ 17,80
Cover for Ø 76 ground socket without locking mechanism	N563	0.3 kg	€ 1,10
Cover for Ø 76 ground socket with locking mechanism (open by Multipurpose wrench)	N564	0.7 kg	€ 2,60
Ground socket for Barrier post Sq 70 x 70 mm without locking mechanism	541-A1	4.4 kg	€ 16,10
Ground socket for Barrier post Sq 70 x 70 mm with locking mechanism	541-A2	4.4 kg	€ 16,10
Cover for Sq 70 x 70 mm ground socket without locking mechanism	N565	0.4 kg	€ 1,50
Cover for Sq 70 x 70 mm ground socket with locking mechanism (open by Multipurpose wrench)	N566	0.8 kg	€ 3,00



Ø 60 mm
Series N565D



Ø 60 mm
Series N566D



Ø 76 mm
Series N575D



Ø 82 mm
Series N584D



Ø 82 mm
Series N585D



Ø 89 mm
Series N588D

Ø 76 mm
Series N574D

Ø 76 mm
Series N578D

Ø 102 mm
Series N592D



Ø 60 mm
Series N568D



Ø 60 mm / Ø 82 mm
Series N564D/N582D



Ø 82 mm
Series N580D



Ø 82 mm
Series N581D



Ø 76 mm
Series N577D



Ø 76 mm
Series N5074D

Ø 89 mm
Series N587D

Ø 150 mm / Ø 193 mm
Series N50155D / N5195D

Ø 102mm
Series N596D

Ø 89 mm
Series N5084D

Ø 102 mm
Series N594D

Ø 100 mm
Series N50101D

Ø 120 mm



Ø 60 / 110 mm
Series N590D



Ø 72 / 160 mm
Series N595D
Pages 69 / 70



Ø 76 / 100 mm
Series N579D



Ø 76 / 102 mm
Series N50102D



Ø 96 / 168 mm
Series N50168D



Ø 108 mm
Series N597D



Ø 140 mm
Series N50140D



70 x 70 mm
Series N573D



70 x 70 mm
Series N5073D



70 x 70 mm
Series N50731D



70 x 70 mm
Series N5071D


100 x 100 mm
Series N5075D



2. Work Site Protection



Industrial safety bollards - Protect people, buildings, assets and etc.



Article.

Stationary Ø 60 x 2.6mm bollards for casting in concrete, above ground 900mm
 Stationary Ø 76 x 2.6mm bollards for casting in concrete, above ground 900mm
 Stationary Ø 101 x 3.0mm bollards for casting in concrete, above ground 900mm
 Stationary Ø 152 x 3.6mm bollards for casting in concrete, above ground 1200mm
 Stationary Ø 152 x 3.6mm bollards for casting in concrete, above ground 1500mm
 Stationary Ø 152 x 3.6mm bollards for casting in concrete, above ground 2000mm
 Stationary Ø 193 x 3.6mm bollards for casting in concrete, above ground 1200mm
 Stationary Ø 193 x 3.6mm bollards for casting in concrete, above ground 1500mm
 Stationary Ø 193 x 3.6mm bollards for casting in concrete, above ground 2000mm
 Stationary Ø 273 x 5mm bollards for casting in concrete, above ground 1500mm
 Stationary Ø 273 x 5mm bollards for casting in concrete, above ground 2000mm

Article no.

66-60-Typ1
 66-76-Typ1
 66-101-Typ1
 66-152-Typ1-A
 66-152-Typ1-B
 66-152-Typ1-C
 66-193-Typ1-A
 66-193-Typ1-B
 66-193-Typ1-C
 66-273-Typ1-A
 66-273-Typ1-B

Weight.


Price (DAP)

5.3 kg
 6.8 kg
 10.4 kg
 17.5 kg
 21.6 kg
 28.6 kg
 22.4 kg
 27.8 kg
 36.7 kg
 54.4 kg
 72.0 kg
 € 17,50
 € 22,50
 € 43,95
 € 65,00
 € 76,00
 € 88,00
 € 89,00
 € 102,10
 € 125,60
 € 215,00
 € 310,00



These post are Hot Dip Galvanized and Signal yellow coated (RAL1003) with three 3M reflective Jet Black stripes (RAL 9005) furthermore order on customized size is accepted.

Note: Order also accepted with only Hot Dip Galvanizing



Article.

Stationary Ø 60 x 2.6mm bollards to be fixed by plug, above ground 900mm
 Stationary Ø 76 x 2.6mm bollards to be fixed by plug, above ground 900mm
 Stationary Ø 101 x 3.0mm bollards to be fixed by plug, above ground 1000mm
 Stationary Ø 152 x 3.2mm bollards to be fixed by plug, above ground 1000mm
 Stationary Ø 152 x 3.2mm bollards to be fixed by plug, above ground 1500mm
 Stationary Ø 193 x 3.6mm bollards to be fixed by plug, above ground 1200mm
 Stationary Ø 193 x 3.6mm bollards to be fixed by plug, above ground 1500mm
 Stationary Ø 273 x 5.0mm bollards for be fixed by plug, above ground 1200mm
 Stationary Ø 273 x 5.0mm bollards for be fixed by plug, above ground 1500mm

Article no.

Article no.	Weight.	Price (DAP)
66-60-Typ2	4.7 kg	€ 16,10
66-76-Typ2	6.0 kg	€ 20,50
66-101-Typ2	10.5 kg	€ 46,10
66-152-Typ2-A	16.1 kg	€ 76,83
66-152-Typ2-B	22.3 kg	€ 105,37
66-193-Typ2-A	30.6 kg	€ 127,32
66-193-Typ2-B	xx.x kg	€ xx,xx
66-273-Typ2-A	xx.x kg	€ xx,xx
66-273-Typ2-B	62.5 kg	€ 267,80





These post are Hot Dip Galvanized and Signal yellow coated (RAL1003) with three 3M reflective Jet Black stripes (RAL 9005) furthermore order on customized size is accepted.

Note: Order also accepted with only Hot Dip Galvanizing

bollards with locking mechanism

bollards without locking mechanism



Article.

Removable Ø 152 x 3.6mm bollards without locking mechanism, above ground 1500mm
 Removable Ø 152 x 3.6mm bollards without locking mechanism, above ground 2000mm
 Removable Ø 193 x 3.6mm bollards without locking mechanism, above ground 1500mm
 Removable Ø 193 x 3.6mm bollards without locking mechanism, above ground 2000mm
 Removable Ø 152 x 3.6mm bollards with triangular locking mechanism, above ground 1000mm
 Removable Ø 193 x 3.6mm bollards with triangular locking mechanism, above ground 1000mm

Article no.

66-152-Typ5-A
 66-152-Typ5-B
 66-193-Typ3-A
 66-193-Typ3-B
 66-152-Typ4
 66-193-Typ4

Weight.

32.3 kg
 36.7 kg
 41.8 kg
 50.8 kg
 22.8 kg
 27.6 kg

Price (DAP)

€ 104,00
 € 134,50
 € 156,00
 € 188,00
 € 116,00
 € 160,00




These post are Hot Dip Galvanized and Signal yellow coated (RAL1003) with three 3M reflective Jet Black stripes (RAL 9005) furthermore order on customized size is accepted.

Note: Order also accepted with only Hot Dip Galvanizing



Safety Hoop - Protection for entrance, ramps, separations, etc.



Article. for Casting in concrete

Barrier Loop Ø 48 x 2.6mm, Height 1000mm x Width 1000mm
 Barrier Loop Ø 48 x 2.6mm, Height 1000mm x Width 1500mm
 Barrier Loop Ø 48 x 2.6mm, Height 1000mm x Width 2000mm
 Barrier Loop Ø 60 x 2.6mm, Height 1000mm x Width 1000mm
 Barrier Loop Ø 60 x 2.6mm, Height 1000mm x Width 1500mm
 Barrier Loop Ø 60 x 2.6mm, Height 1000mm x Width 2000mm

Article. for Plugging down

Barrier Loop Ø 48 x 2.6mm, Height 1000mm x Width 1000mm
 Barrier Loop Ø 48 x 2.6mm, Height 1000mm x Width 1500mm
 Barrier Loop Ø 48 x 2.6mm, Height 1000mm x Width 2000mm
 Barrier Loop Ø 60 x 2.6mm, Height 1000mm x Width 1000mm
 Barrier Loop Ø 60 x 2.6mm, Height 1000mm x Width 1500mm
 Barrier Loop Ø 60 x 2.6mm, Height 1000mm x Width 2000mm

Article. for Wall mounting

Barrier Loop Ø 48 x 2.6mm, Height 1000mm x Width 700mm
 Barrier Loop Ø 48 x 2.6mm, Height 1000mm x Width 1000mm
 Barrier Loop Ø 48 x 2.6mm, Height 1000mm x Width 1200mm
 Barrier Loop Ø 60 x 2.6mm, Height 1000mm x Width 700mm
 Barrier Loop Ø 60 x 2.6mm, Height 1000mm x Width 1000mm
 Barrier Loop Ø 60 x 2.6mm, Height 1000mm x Width 1200mm


Article no.	Weight.	Price (DAP)
33-48-Typ1-1m	12.8 kg	€ 42,50
33-48-Typ1-1.5m	15.8 kg	€ 52,00
33-48-Typ1-2m	18.8 kg	€ 62,00
33-60-Typ1-1m	15.7 kg	€ 52,00
33-60-Typ1-1.5m	19.7 kg	€ 65,00
33-60-Typ1-2m	24.3 kg	€ 80,00
33-48-Typ2-1m	12.4 kg	€ 40,90
33-48-Typ2-1.5m	15.4 kg	€ 51,00
33-48-Typ2-2m	20.2 kg	€ 66,70
33-60-Typ2-1m	16.5 kg	€ 54,50
33-60-Typ2-1.5m	20.5 kg	€ 68,00
33-60-Typ2-2m	24.3 kg	€ 80,00
33-48-Typ3-0.7m	11.5 kg	€ 38,00
33-48-Typ3-1m	13.5 kg	€ 44,00
33-48-Typ3-1.2m	14.5 kg	€ 48,00
33-60-Typ3-0.7m	14.5 kg	€ 47,50
33-60-Typ3-1m	18.9 kg	€ 62,50
33-60-Typ3-1.2m	19.5 kg	€ 64,50



These post are Hot Dip Galvanized and Signal yellow coated (RAL1003) with 3M reflective Jet Black stripes (RAL 9005) furthermore order on customized size is accepted.

Note: Order also accepted with only Hot Dip Galvanizing

Safety Hoop - Effective protection for indoor and outdoor areas, warehouses and production halls. To secure work areas and traffic lanes, protect machines, columns and racks.



Article. for Casting in concrete

Barrier Loop Ø 76 x 2.6mm, Height 250mm x Width 400mm
 Barrier Loop Ø 76 x 2.6mm, Height 250mm x Width 750mm
 Barrier Loop Ø 76 x 2.6mm, Height 250mm x Width 1000mm
 Barrier Loop Ø 76 x 2.6mm, Height 650mm x Width 400mm
 Barrier Loop Ø 76 x 2.6mm, Height 650mm x Width 750mm
 Barrier Loop Ø 76 x 2.6mm, Height 650mm x Width 1000mm
 Barrier Loop Ø 76 x 2.6mm, Height 1150mm x Width 400mm
 Barrier Loop Ø 76 x 2.6mm, Height 1150mm x Width 750mm
 Barrier Loop Ø 76 x 2.6mm, Height 1150mm x Width 1000mm

Article. for Plugging down

Barrier Loop Ø 76 x 3mm, Height 250mm x Width 400mm
 Barrier Loop Ø 76 x 3mm, Height 250mm x Width 750mm
 Barrier Loop Ø 76 x 3mm, Height 250mm x Width 1000mm
 Barrier Loop Ø 76 x 3mm, Height 650mm x Width 400mm
 Barrier Loop Ø 76 x 3mm, Height 650mm x Width 750mm
 Barrier Loop Ø 76 x 3mm, Height 650mm x Width 1000mm
 Barrier Loop Ø 76 x 3mm, Height 1150mm x Width 400mm
 Barrier Loop Ø 76 x 3mm, Height 1150mm x Width 750mm
 Barrier Loop Ø 76 x 3mm, Height 1150mm x Width 1000mm

Article no.	Weight.	Price (DAP)
33-76-Typ1-A	6.2 kg	€ 20,50
33-76-Typ1-B	7.8 kg	€ 26,00
33-76-Typ1-C	9.1 kg	€ 30,00
33-76-Typ1-D	10.2 kg	€ 33,80
33-76-Typ1-E	11.8 kg	€ 39,00
33-76-Typ1-F	13.1 kg	€ 43,50
33-76-Typ1-G	15.2 kg	€ 50,10
33-76-Typ1-H	16.8 kg	€ 55,50
33-76-Typ1-I	18.1 kg	€ 60,00




33-76-Typ2-A	5.0 kg	€ 16,50
33-76-Typ2-B	6.8 kg	€ 22,50
33-76-Typ2-C	8.2 kg	€ 27,00
33-76-Typ2-D	9.5 kg	€ 31,50
33-76-Typ2-E	11.3 kg	€ 37,50
33-76-Typ2-F	12.7 kg	€ 42,00
33-76-Typ2-G	15.1 kg	€ 50,00
33-76-Typ2-H	16.8 kg	€ 55,50
33-76-Typ2-I	18.2 kg	€ 60,00



These post are Hot Dip Galvanized and Signal yellow coated (RAL1003) with 3M reflective Jet Black stripes (RAL 9005) furthermore order on customized size is accepted.

Note: Order also accepted with only Hot Dip Galvanizing

Safety Hoop - For temporary opening/closing of entrances. Locked with hexagon socket screws, the hoop can be detached from the plates and inserted as needed.



Article. Detachable barrier post for plugging down

Detachable Ø 76 x 2.6mm barrier post, above ground 1000mm

Detachable Sq. 70 x 70 x 2.6mm barrier post, above ground 100mm

Article no.

66-76-Typ3

66-70-Typ3

Weight.

7.8 kg

7.9 kg

Price (DAP)

€ 44,30

€ 46,00

Article. Detachable anti-nudge hoop for plugging down

Detachable anti-nudge hoop Ø 76 x 3mm, Height 650mm x Width 400mm

Detachable anti-nudge hoop Ø 76 x 3mm, Height 650mm x Width 750mm

Detachable anti-nudge hoop Ø 76 x 3mm, Height 650mm x Width 1000mm

Detachable anti-nudge hoop Ø 76 x 3mm, Height 1150mm x Width 400mm

Detachable anti-nudge hoop Ø 76 x 3mm, Height 1150mm x Width 750mm

Detachable anti-nudge hoop Ø 76 x 3mm, Height 1150mm x Width 1000mm

33-76-Typ3-A

33-76-Typ3-B

33-76-Typ3-C

33-76-Typ3-D

33-76-Typ3-E

33-76-Typ3-F

12.7 kg

15.1 kg

16.5 kg

18.9 kg

20.7 kg

22.0 kg

€ 47,00

€ 55,50

€ 60,50

€ 69,50



€ 76,00

€ 81,00



These post are Hot Dip Galvanized and Signal yellow coated (RAL1003) with three 3M reflective Jet Black stripes (RAL 9005) furthermore order on customized size is accepted.

Note: Order also accepted with only Hot Dip Galvanizing



Article. Impact resistance barrier post for plugging down

Impact Ø 76 x 2.6mm barrier post, above ground 1000mm
Impact Ø 152 x 3.6mm barrier post, above ground 1000mm
Impact Sq. 70 x 70 x 2.6mm barrier post, above ground 100mm

Article no.

66-76-Typ4
66-152-Typ3
66-70-Typ4

Weight.

9.2 kg
24.2 kg
9.3 kg

Price (DAP)

€ 39,60
€ 106,00
€ 41,30

Article. Impact resistance anti-nudge hoop for plugging down

Impact anti-nudge hoop Ø 76 x 3mm, Height 650mm x Width 400mm
Impact anti-nudge hoop Ø 76 x 3mm, Height 650mm x Width 750mm
Impact anti-nudge hoop Ø 76 x 3mm, Height 650mm x Width 1000mm
Impact anti-nudge hoop Ø 76 x 3mm, Height 1150mm x Width 400mm
Impact anti-nudge hoop Ø 76 x 3mm, Height 1150mm x Width 750mm
Impact anti-nudge hoop Ø 76 x 3mm, Height 1150mm x Width 1000mm

33-76-Typ4-A
33-76-Typ4-B
33-76-Typ4-C
33-76-Typ4-D
33-76-Typ4-E
33-76-Typ4-F

15.9 kg
17.7 kg
19.1 kg
21.5 kg
23.3 kg
24.6 kg


€ 58,50
€ 65,00
€ 70,00
€ 79,00
€ 86,00
€ 90,50




These post are Hot Dip Galvanized and Signal yellow coated (RAL1003) with three 3M reflective Jet Black stripes (RAL 9005) furthermore order on customized size is accepted.

Note: Order also accepted with only Hot Dip Galvanizing


Anti-nudge hoop Ø 76 mm



Anti-nudge hoop 90° single sided



Anti-nudge hoop 90° double sided



Article. Anti-nudge hoop 90° single sided for casting in concrete

Anti-nudge hoop Ø 76 x 3mm, Height 650mm x Width 400mm
 Anti-nudge hoop Ø 76 x 3mm, Height 1150mm x Width 400mm
 Anti-nudge hoop Ø 76 x 3mm, Height 650mm x Width 600mm
 Anti-nudge hoop Ø 76 x 3mm, Height 1150mm x Width 600mm

Article. Anti-nudge hoop 90° single sided for plugging down

Anti-nudge hoop Ø 76 x 3mm, Height 650mm x Width 400mm
 Anti-nudge hoop Ø 76 x 3mm, Height 1150mm x Width 400mm
 Anti-nudge hoop Ø 76 x 3mm, Height 650mm x Width 600mm
 Anti-nudge hoop Ø 76 x 3mm, Height 1150mm x Width 600mm

Article. Anti-nudge hoop 90° double sided for casting in concrete

Anti-nudge hoop Ø 76 x 3mm, Height 650mm x Length 400mm x Width 750mm
 Anti-nudge hoop Ø 76 x 3mm, Height 1150mm x Length 400mm x Width 750mm
 Anti-nudge hoop Ø 76 x 3mm, Height 650mm x Length 400mm x Width 1000mm
 Anti-nudge hoop Ø 76 x 3mm, Height 1150mm x Length 400mm x Width 1000mm

Article. Anti-nudge hoop 90° double sided for plugging down


Anti-nudge hoop Ø 76 x 3mm, Height 650mm x Length 400mm x Width 750mm
 Anti-nudge hoop Ø 76 x 3mm, Height 1150mm x Length 400mm x Width 750mm
 Anti-nudge hoop Ø 76 x 3mm, Height 650mm x Length 400mm x Width 1000mm
 Anti-nudge hoop Ø 76 x 3mm, Height 1150mm x Length 400mm x Width 1000mm

Article no.	Weight.	Price (DAP)
67-3L-76-Typ1-A	19.0 kg	€ 93,00
67-3L-76-Typ1-B	25.0 kg	€ 123,00
67-3L-76-Typ1-C	22.0 kg	€ 108,00
67-3L-76-Typ1-D	27.5 kg	€ 135,00
67-3L-76-Typ2-A	15.2 kg	€ 75,00
67-3L-76-Typ2-B	23.5 kg	€ 115,00
67-3L-76-Typ2-C	17.3 kg	€ 85,00
67-3L-76-Typ2-D	25.1 kg	€ 126,00
67-4L-76-Typ1-A	28.5 kg	€ 140,00
67-4L-76-Typ1-B	36.0 kg	€ 178,00
67-4L-76-Typ1-C	30.0 kg	€ 148,00
67-4L-76-Typ1-D	37.5 kg	€ 184,00
67-4L-76-Typ2-A	22.1 kg	€ 108,00
67-4L-76-Typ2-B	33.3 kg	€ 163,00
67-4L-76-Typ2-C	25.8 kg	€ 108,00
67-4L-76-Typ2-D	36.9 kg	€ 160,00





These post are Hot Dip Galvanized and Signal yellow coated (RAL1003) with 3M reflective Jet Black stripes (RAL 9005) furthermore order on customized size is accepted.

Note: Order also accepted with only Hot Dip Galvanizing



Anti-nudge hoop 90° single sided (deep)

Anti-nudge hoop 90° double sided (deep)

**Article. Anti-nudge hoop 90° single sided for casting in concrete (Deep)**

- Anti-nudge hoop Ø 76 x 3mm, Height 650mm x Length 400mm x Width 600mm (Right)
- Anti-nudge hoop Ø 76 x 3mm, Height 650mm x Length 400mm x Width 600mm (Left)
- Anti-nudge hoop Ø 76 x 3mm, Height 1150mm x Length 400mm x Width 600mm (Right)
- Anti-nudge hoop Ø 76 x 3mm, Height 1150mm x Length 400mm x Width 600mm (Left)

Article. Anti-nudge hoop 90° single sided for plugging down (Deep)

- Anti-nudge hoop Ø 76 x 3mm, Height 650mm x Length 400mm x Width 600mm (Right)
- Anti-nudge hoop Ø 76 x 3mm, Height 650mm x Length 400mm x Width 600mm (Left)
- Anti-nudge hoop Ø 76 x 3mm, Height 1150mm x Length 400mm x Width 600mm (Right)
- Anti-nudge hoop Ø 76 x 3mm, Height 1150mm x Length 400mm x Width 600mm (Left)

Article. Anti-nudge hoop 90° double sided for casting in concrete (Deep)

- Anti-nudge hoop Ø 76 x 3mm, Height 650mm x Length 400mm x Width 750mm
- Anti-nudge hoop Ø 76 x 3mm, Height 650mm x Length 400mm x Width 1000mm
- Anti-nudge hoop Ø 76 x 3mm, Height 1150mm x Length 400mm x Width 750mm
- Anti-nudge hoop Ø 76 x 3mm, Height 1150mm x Length 400mm x Width 1000mm

Article. Anti-nudge hoop 90° double sided for plugging down (Deep)

- Anti-nudge hoop Ø 76 x 3mm, Height 650mm x Length 400mm x Width 750mm
- Anti-nudge hoop Ø 76 x 3mm, Height 650mm x Length 400mm x Width 1000mm
- Anti-nudge hoop Ø 76 x 3mm, Height 1150mm x Length 400mm x Width 750mm
- Anti-nudge hoop Ø 76 x 3mm, Height 1150mm x Length 400mm x Width 1000mm

Article no.	Weight.	Price (DAP)
67-51-Typ1-AR	14.0 kg	€ 50,00
67-51-Typ1-BL	14.0 kg	€ 50,00
67-51-Typ1-CR	19.5 kg	€ 63,00
67-51-Typ1-DL	19.5 kg	€ 63,00
67-51-Typ2-AR	12.0 kg	€ 44,00
67-51-Typ2-BL	12.0 kg	€ 44,00
67-51-Typ2-CR	17.6 kg	€ 65,00
67-51-Typ2-DL	17.6 kg	€ 65,00
67-51-Typ1-A	14.7 kg	€ 91,30
67-51-Typ1-B	17.5 kg	€ 94,20
67-51-Typ1-C	19.5 kg	€ 99,50
67-51-Typ1-D	21.0 kg	€ 103,90
67-51-Typ2-A	13.1 kg	€ 103,00
67-51-Typ2-B	15.7 kg	€ 106,00
67-51-Typ2-C	17.1 kg	€ 112,00
67-51-Typ2-D	19.4 kg	€ 116,00



These post are Hot Dip Galvanized and Signal yellow coated (RAL1003) with three 3M reflective Jet Black stripes (RAL 9005) furthermore order on customized size is accepted.

Note: Order also accepted with only Hot Dip Galvanizing



Safety Hoop - protection for posts, pillars, poles, etc.

Anti-nudge hoop for posts



Crash guard with covered



Article. Anti-nudge hoop for plugging down

Anti-nudge hoop Ø 60 x 2.6mm, Height 650mm x Length 600mm x Width 600mm
Anti-nudge hoop Ø 60 x 2.6mm, Height 800mm x Length 800mm x Width 800mm

Article no.

67-55-Typ1-A
67-55-Typ1-B

Weight.

18.3 kg
21.0 kg

Price (DAP)

€ 100,00
€ 116,00

Article. Crash guard with covered for plugging down

Crash guard with covered Ø 76 x 3mm, Height 650mm x Width 750mm
Crash guard with covered Ø 76 x 3mm, Height 650mm x Width 1000mm

67-90-Typ1-A
67-90-Typ1-B


18.1 kg
22.1 kg

€ 83,10
€ 88,50



These post are Hot Dip Galvanized and Signal yellow coated (RAL1003) with 3M reflective Jet Black stripes (RAL 9005) furthermore order on customized size is accepted.

Note: Order also accepted with only Hot Dip Galvanizing



Article. Anti-nudge bar of Ø76mm for plugging down (Refer A)

Anti-nudge hoop Ø 76 x 3mm, Height 86mm x Width 400mm
 Anti-nudge hoop Ø 76 x 3mm, Height 86mm x Width 800mm
 Anti-nudge hoop Ø 76 x 3mm, Height 86mm x Width 1000mm
 Anti-nudge hoop Ø 76 x 3mm, Height 86mm x Width 1200mm

Article. Corner anti-nudge bar of Ø76mm for plugging down (Refer B)

Anti-nudge hoop Ø 76 x 3mm, Height 86mm x Width 700 x 700mm

Article. Anti-nudge hoop of Ø60mm for plugging down (Refer C)

Anti-nudge hoop Ø 60 x 3mm, Height 115mm x Width 400mm
 Anti-nudge hoop Ø 60 x 3mm, Height 115mm x Width 1000mm
 Anti-nudge hoop Ø 60 x 3mm, Height 115mm x Width 1500mm
 Anti-nudge hoop Ø 60 x 3mm, Height 115mm x Width 2000mm

Article. Anti-nudge hoop for truck pull in assist of Ø152mm for plugging down (Refer D)

Anti-nudge hoop Ø 152 x 3mm (Left)
 Anti-nudge hoop Ø 152 x 3mm (Right)
 Anti-nudge hoop Ø 152 x 3mm (Straight extension)

Article no.	Weight.	Price (DAP)
67-89-Typ2-A	3.7 kg	€ 23,00
67-89-Typ2-B	5.7 kg	€ 25,80
67-89-Typ2-C	6.7 kg	€ 28,50
67-89-Typ2-D	7.7 kg	€ 31,20
67-90-Typ2	9.0 kg	€ 32,00
67-89-Typ1-A	3.2 kg	€ 14,00
67-89-Typ1-B	5.5 kg	€ 25,00
67-89-Typ1-C	7.5 kg	€ 33,00
67-89-Typ1-D	9.4 kg	€ 42,00
67-90-Typ3-L	53.0 kg	€ 159,00
67-90-Typ3-R	53.0 kg	€ 159,00
67-90-Typ3-S	59.4 kg	€ 149,00




These post are Hot Dip Galvanized and Signal yellow coated (RAL1003) with 3M reflective Jet Black stripes (RAL 9005)

Note: Order also accepted with only Hot Dip Galvanizing



Protective railing - Anti-nudge railing as safety railing for work ways in front of machines, robots, racks, etc. The railing system is available for plugging with or without base plate, removable and tiltable up to 30°

Steel tube 70 x 70 mm with top and knee bars of steel tube 60 x 40 mm, height approx. 1000 mm, bolted



Article. Post for protective railing for plugging down

End post of Sq. 70 x 70 x 2.5mm

Middle post of Sq. 70 x 70 x 2.5mm

Corner post of Sq. 70 x 70 x 2.5mm

Article. Cross bar for protective railing

Cross bar of Sq. 70 x 70 x 2.5mm = Length 800mm

Cross bar of Sq. 70 x 70 x 2.5mm = Length 1300mm

Cross bar of Sq. 70 x 70 x 2.5mm = Length 1800mm


Cross bar of Sq. 70 x 70 x 2.5mm = Length 2300mm

Article no.	Weight.	Price (DAP)
69-70-Typ1-A	6.5 kg	€ 38,00
69-70-Typ1-B	7.0 kg	€ 41,50
69-70-Typ1-C	7.0 kg	€ 42,50
69-48-P14	3.1 kg	€ 9,50
69-48-P15	5.1 kg	€ 15,80
69-48-P16	7.1 kg	€ 18,80
69-48-P17	9.0 kg	€ 27,50



These post are Hot Dip Galvanized and Signal yellow coated (RAL1003) with 3M reflective Jet Black stripes (RAL 9005)

Note: Order also accepted with only Hot Dip Galvanizing

**Article. Impact resistance Post for protective railing for plugging down**

Impact resistance End post of Sq. 70 x 70 x 2.5mm

Impact resistance Middle post of Sq. 70 x 70 x 2.5mm

Article no.

69-70-Typ3-A

69-70-Typ3-B

Weight.

9.8 kg

10.2 kg

Price (DAP)

€ 55,30

€ 58,60

Article. Detachable Post for protective railing for plugging down

Detachable End post of Sq. 70 x 70 x 2.5mm

Detachable Middle post of Sq. 70 x 70 x 2.5mm

Detachable Corner post of Sq. 70 x 70 x 2.5mm

69-70-Typ2-A

69-70-Typ2-B

69-70-Typ2-C

8.5 kg

9.0 kg

9.0 kg

€ 59,50

€ 63,00


€ 64,00



These post are Hot Dip Galvanized and Signal yellow coated (RAL1003) with 3M reflective Jet Black stripes (RAL 9005)

Note: Order also accepted with only Hot Dip Galvanizing

Protective railing - Railing system for universal use, e.g. as internal protective railing to separate traffic aisles or protect terminal boxes, distribution panels, machines, etc. Assembly is easy as that: Put the parts together, plug down,



Article. Post for protective railing for plugging down

- End post of Ø 48 x 2.6mm
- Middle post of Ø 48 x 2.6mm
- Corner post of Ø 48 x 2.6mm

Article. Cross bar for protective railing

- Cross bar of Ø 48 x 2.6mm = Length 500mm
- Cross bar of Ø 48 x 2.6mm = Length 1000mm
- Cross bar of Ø 48 x 2.6mm = Length 1500mm

Article. Railing handle wall mounting

- Railing handle, Height 1200mm x Width 250mm
- Railing handle, Height 2000mm x Width 250mm

Article no.	Weight.	Price (DAP)
69-48-Typ1-A	4.9 kg	€ 26,20
69-48-Typ1-B	7.2 kg	€ 27,20
69-48-Typ1-C	7.0 kg	€ 28,10
69-48-P8	1.5 kg	€ 4,60
69-48-P9	3.11 kg	€ 9,50
69-48-P10	4.7 kg	€ 14,50
67-89-Typ3-A	6.1 kg	€ 26,00
67-89-Typ3-B	8.5 kg	€ 36,50




These post are Hot Dip Galvanized and Signal yellow coated (RAL1003) with 3M reflective Jet Black stripes (RAL 9005)

Note: Order also accepted with only Hot Dip Galvanizing

Crash guard angle- acc. to BGR234 for individual use (warehouse equipment, rack or shelf supports, etc.)

Crash guard angle, Article no. 69-47-P9 (Refer A) - To protect shelves and storage racks. The new crash guard can be tilted 15°. This compensates impacts from fork trucks or other vehicles without damage or being torn out of the floor (up to 400Nm pressure).



Article. Crash guard angle with impact resistance up to 15° (Refer A)

Impact crash guard, Height 400 x Length 160 x Thickness 6mm

Article. Crash guard angle (Refer B)

Crash guard, Height 200 x Length 160 x Thickness 6mm

Crash guard, Height 400 x Length 160 x Thickness 6mm

Crash guard, Height 800 x Length 160 x Thickness 6mm

Crash guard, Height 1200 x Length 160 x Thickness 6mm

Article. Crash guard angle with reinforced edges (Refer C)

Crash guard, Height 400 x Length 160 x Thickness 6mm

Crash guard, Height 800 x Length 160 x Thickness 6mm

Crash guard, Height 1200 x Length 160 x Thickness 6mm

Article. Crash guard U shape with reinforced edges (Refer D)

Crash guard, Height 400 x Length 160 x width 160 x Thickness 6mm

Article no.	Weight.	Price (DAP)
69-47-Typ4	6.0 kg	€ 37,00
69-47-Typ1-A	3.0 kg	€ 13,20
69-47-Typ1-B	5.5 kg	€ 21,00
69-47-Typ1-C	10.7 kg	€ 40,00
69-47-Typ1-D	16.0 kg	€ 60,00
69-47-Typ2-A	7.5 kg	€ 29,00
69-47-Typ2-B	14.5 kg	€ 56,00
69-47-Typ2-C	21.5 kg	€ 79,00
69-47-Typ3	10.8 kg	€ 36,72



These post are Hot Dip Galvanized and Signal yellow coated (RAL1003) with 3M reflective Jet Black stripes (RAL 9005)

Note: Order also accepted with only Hot Dip Galvanizing

Know INDIA - Kathakali, Kathak is a major form of classical Indian dance. It is a "story play" genre of art, but one distinguished by the elaborately colorful make-up, costumes and face masks that the traditionally male actor-dancers wear.





3. Bicycle rack



Bicycle rack - Sturdy and space-saving due to alternating high and low racks. Racks can be bolted to form a serial system, with boreholes for anchoring or plugging.



Bicycle rack - Sturdy and space-saving due to alternating high and low racks. Racks can be bolted to form a serial system, with boreholes for anchoring or plugging.

Article.

Bicycle rack - one side for 3 bicycle, space between bicycle 350mm

Bicycle rack - one side for 4 bicycle

Bicycle rack - one side for 5 bicycle

Bicycle rack - one side for 6 bicycle

Bicycle rack - two side for 2 x 3 bicycle, space between bicycle 350mm

Bicycle rack - two side for 2 x 5 bicycle

Bicycle rack - two side for 2 x 6 bicycle

Bicycle rack - one side for 3 bicycle, space between bicycle 350mm

Article no.

92-1-3

92-1-4

92-1-5

92-1-6

92-2-3

92-2-5

92-2-6

92-3-21

Weight.

10.0 kg

14.5 kg

16.5 kg

20.0 kg

16.0 kg

26.0 kg

32.0 kg

15.0 kg

Price (DAP)

€ 18.10

€ 16.50

€ 38.50

€ 49.80

€ 27.10

€ 30.10

€ 43.50

€ 35.80



These rack are Hot Dip Galvanized Frame of angular section Hoop 19 mm round tube, approximate hight is 510 mm, Bicycle wheel width up to 55 mm. space between bicycles 350 mm

Note: Order also accepted with only color coated

Bicycle rack - Sturdy and weatherproof parking rack made of Ø 12 mm round steel with welded square tube strut 40 x 40 mm. Vertical tube can be fixed by bolts. Height approx. 500 mm above ground, for bicycle wheel width up to 55 mm, hot-dip galvanized



Bicycle rack fixed by casting in concrete, with 45° positioning



Bicycle rack fixed by wall brackets, with 45° positioning



Bicycle rack fixed by plugging down

Article.

Bicycle rack for six bicycle, for casting in concrete. (Angled positioning 45°)
 Bicycle rack for six bicycle, for casting in concrete. (Straight positioning 90°)

Bicycle rack for six bicycle, for plugging down. (Angled positioning 45°)
 Bicycle rack for six bicycle, for plugging down. (Straight positioning 90°)

Bicycle rack for six bicycle, for wall brackets. (Angled positioning 45°)
 Bicycle rack for six bicycle, for wall brackets. (Straight positioning 90°)

Article no.

92-4-1-6L
 92-4-1-6S

Weight.

20.7 kg
 21.2 kg

Price (DAP)

€ 18.10
 € 16.50

92-4-2-6L
 92-4-2-6S

20.0 kg
 20.3 kg

€ 49.80
 € 27.10

92-4-3-6L
 92-4-3-6S

18.0 kg
 18.4 kg


€ 43.50
 € 35.80



Note: Order also accepted with only color coated



Bicycle rack - Sturdy and weatherproof parking rack made of Ø 12 mm round steel with welded square tube strut 40 x 40 mm. Vertical tube can be fixed by bolts. Height approx. 500 mm above ground, for bicycle wheel width up to 55 mm, hot-dip galvanized



Article.

Bicycle rack one side parking, for casting in concrete.
Bicycle rack two side parking, for casting in concrete.

Bicycle rack one side parking, for plugging down.
Bicycle rack two side parking, for plugging down.

Bicycle rack for wall brackets. (Angled positioning 45°)
Bicycle rack for wall brackets. (Straight positioning 90°)

Article no.

92-5-1S
92-5-2S

92-6-1S
92-6-2S

92-7-1S
92-7-1L

Weight.

2.7 kg
4.0 kg

2.7 kg
4.0 kg

2.4 kg
1.7 kg

Price (DAP)

€ 18.10
€ 16.50

€ 49.80
€ 27.10

€ 43.50
€ 35.80



Note: Order also accepted with only color coated

**Article.**

Bicycle stand - lean on hoop
 Bicycle stand - lean on hoop
 Bicycle stand - Single parking made of square tube
 Bicycle stand - loop

Article no.

92-4-1-6L
 92-4-1-6S

Weight.

20.7 kg
 21.2 kg

Price (DAP)


€ 18.10
 € 16.50



Note: Order also accepted with only color coated



Lean-on hoop made of steel tube - for casting in concrete, Hot-dip galvanized and optionally powder-coated in DB 703. total height: approx. 1200 mm




Article. Sq tube 80 x 20mm

Bicycle Loop, Height 1000mm x Width 450mm (without cross bar)
Bicycle Loop, Height 1000mm x Width 750mm (without cross bar)
Bicycle Loop, Height 1000mm x Width 1000mm (without cross bar)
Bicycle Loop, Height 1000mm x Width 450mm (with cross bar)
Bicycle Loop, Height 1000mm x Width 750mm (with cross bar)
Bicycle Loop, Height 1000mm x Width 1000mm (with cross bar)
Bicycle Loop, Height 1000mm x Width 450mm (without cross bar, small distance)
Bicycle Loop, Height 1000mm x Width 750mm (without cross bar, small distance)
Bicycle Loop, Height 1000mm x Width 1000mm (without cross bar, small distance)

Article no.	Weight.	Price (DAP)
92-58-045	8.5 kg	€38.50
92-58-075	9.5 kg	€ 38.50
92-58-100	10.0 kg	€ 38.50
92-59-045	10.0 kg	€ 38.50
92-59-075	11.5 kg	€ 38.50
92-59-100	13.0 kg	€ 38.50
92-60-045	10.0 kg	€ 38.50
92-60-075	11.5 kg	€ 38.50
92-60-100	13.0 kg	€ 38.50



Lean-on hoop made of steel tube - for casting in concrete, Hot-dip galvanized and optionally powder-coated in DB 703. total height: approx. 1200 mm



Article. Sq tube 60 x 60mm

Bicycle Loop, Height 1000mm x Width 450mm (without cross bar)
 Bicycle Loop, Height 1000mm x Width 750mm (without cross bar)
 Bicycle Loop, Height 1000mm x Width 1000mm (without cross bar)
 Bicycle Loop, Height 1000mm x Width 450mm (with cross bar)
 Bicycle Loop, Height 1000mm x Width 750mm (with cross bar)
 Bicycle Loop, Height 1000mm x Width 1000mm (with cross bar)

Article no.

92-61-045
 92-61-075
 92-61-100
 92-62-045
 92-62-075
 92-62-100

Weight. Price (DAP)


10.0 kg
 11.0 kg
 11.5 kg
 11.0 kg
 13.0 kg
 15.0 kg

Article. Sq tube 60 x 40mm


Bicycle Loop, Height 1000mm x Width 450mm (without cross bar)
 Bicycle Loop, Height 1000mm x Width 750mm (without cross bar)
 Bicycle Loop, Height 1000mm x Width 1000mm (without cross bar)
 Bicycle Loop, Height 1000mm x Width 450mm (with cross bar)
 Bicycle Loop, Height 1000mm x Width 750mm (with cross bar)
 Bicycle Loop, Height 1000mm x Width 1000mm (with cross bar)

92-63-045
 92-63-075
 92-63-100
 92-64-045
 92-64-075
 92-64-100

10.0 kg
 11.5 kg
 12.5 kg
 12.0 kg
 14.0 kg
 16.0 kg



Lean-on hoop of flat bar steel - for casting in concrete, hot-dip galvanized and optionally powder-coated in DB 703 Total height approx. 1200 mm



Article. Flat bar steel 50 x 12 mm

Bicycle Loop, Height 1000mm x Width 450mm (without cross bar)
 Bicycle Loop, Height 1000mm x Width 750mm (without cross bar)
 Bicycle Loop, Height 1000mm x Width 1000mm (without cross bar)
 Bicycle Loop, Height 1000mm x Width 450mm (with cross bar)
 Bicycle Loop, Height 1000mm x Width 750mm (with cross bar)
 Bicycle Loop, Height 1000mm x Width 1000mm (with cross bar)

Article no.

92-65-045
 92-65-075
 92-65-100
 92-66-045
 92-66-075
 92-66-100

Weight. Price (DAP)


13.0 kg
 14.5 kg
 16.0 kg
 15.0 kg
 18.0 kg
 20.5 kg

Article. Flat bar steel 80 x 12 mm

Bicycle Loop, Height 1000mm x Width 450mm (without cross bar)
 Bicycle Loop, Height 1000mm x Width 750mm (without cross bar)
 Bicycle Loop, Height 1000mm x Width 1000mm (without cross bar)
 Bicycle Loop, Height 1000mm x Width 450mm (with cross bar)
 Bicycle Loop, Height 1000mm x Width 750mm (with cross bar)
 Bicycle Loop, Height 1000mm x Width 1000mm (with cross bar)

92-67-045
 92-67-075
 92-67-100
 92-68-045
 92-68-075
 92-68-100

21.0 kg
 23.5 kg
 25.5 kg
 24.5 kg
 29.0 kg
 33.0 kg



Article. Flat bar steel 50 x 12 mm

- Bicycle Loop, Height 1000mm x Width 750mm (without cross bar)
- Bicycle Loop, Height 1000mm x Width 1000mm (without cross bar)
- Bicycle Loop, Height 1000mm x Width 750mm (with cross bar)
- Bicycle Loop, Height 1000mm x Width 1000mm (with cross bar)

Article no.

- 92-69-075
- 92-69-100
- 92-70-075
- 92-70-100

Weight. Price (DAP)

- 14.5 kg
- 16.0 kg
- 18.0 kg
- 20.5 kg

Article. Flat bar steel 80 x 12 mm

- Bicycle Loop, Height 1000mm x Width 750mm (without cross bar)
- Bicycle Loop, Height 1000mm x Width 1000mm (without cross bar)
- Bicycle Loop, Height 1000mm x Width 750mm (with cross bar)
- Bicycle Loop, Height 1000mm x Width 1000mm (with cross bar)

- 92-71-075
- 92-71-100
- 92-72-075
- 92-72-100

- 23.0 kg
- 25.0 kg
- 29.0 kg
- 33.0 kg

Know INDIA - Good Indian food is an balance of flavors (salty, sweet, sour, bitter, hot) and textures... not too much of anything, chili included. Spices prevent our food from spoilage, and we are so much accustomed to eat spicy food. ... It is all because of bacteria and food borne pathogens: The chemical compounds of spices protect their plants as well as our food from food spoilage microbes and bacteria.





4. Barrier Gate

Swiveling gates

can be swiveled horizontally, no supporting post. Locking mechanism can be closed or opened using a locking pin, fitted for a padlock or triangular locking mechanism acc. with DIN 3223 or Euro profile cylinder lock.

Swiveling post: Steel tube Ø 102 mm

Barrier arm: Steel tube Ø 60 mm

Height: Approx. 950 mm above ground




For casting in concrete, hot-dip galvanized

Total width	Approx.kg	For padlock Part-No.	Price €	With triangular lock Part-No.	Price €	With Euro profile cylinder lock Part-No.	Price €
1500 mm	32.0	77-1-15-PH	€ 234,50	77-1-15-TH	€ 294,80	77-1-15-CH	€ 328,30
2000 mm	35.0	77-1-20-PH	€ 247,90	77-1-20-TH	€ 308,20	77-1-20-CH	€ 341,70
2500 mm	38.0	77-1-25-PH	€ 261,30	77-1-25-TH	€ 321,60	77-1-25-CH	€ 355,10
3000 mm	41.0	77-1-30-PH	€ 274,70	77-1-30-TH	€ 335,00	77-1-30-CH	€ 368,50
3500 mm	44.0	77-1-35-PH	€ 288,10	77-1-35-TH	€ 348,40	77-1-35-CH	€ 381,90

For casting in concrete, hot-dip galvanized and red coated with white reflecting rings

Total width	Approx.kg	For padlock Part-No.	Price €	With triangular lock Part-No.	Price €	With Euro profile cylinder lock Part-No.	Price €
1500 mm	32.0	77-1-15-P	€ 274,70	77-1-15-T	€ 335,00	77-1-15-C	€ 361,80
2000 mm	35.0	77-1-20-P	€ 288,10	77-1-20-T	€ 348,40	77-1-20-C	€ 375,20
2500 mm	38.0	77-1-25-P	€ 301,50	77-1-25-T	€ 361,80	77-1-25-C	€ 388,60
3000 mm	41.0	77-1-30-P	€ 341,90	77-1-30-T	€ 375,20	77-1-30-C	€ 402,00
3500 mm	44.0	77-1-35-P	€ 328,30	77-1-35-T	€ 388,60	77-1-35-C	€ 415,40



Optionally available with:

Base plate for plugging down

360 x 360 x 8 mm including 4 holes Ø 21 mm for anchor bolts, hole pitch 260 x 260 mm, for plugging down, add letter P to the part-no.

Swing barrier

barrier swings horizontally with no supporting post. Locking mechanism can be closed or opened using a pin latching automatically in four positions (every 90°), fitted for a padlock or with triangular locking mechanism acc. to DIN 3223 or Euro profile cylinder lock

Swiveling post: Steel tube Ø 102 mm

Barrier arm: Steel tube 60 x 40 mm

Height: Approx. 950 mm above ground




For casting in concrete, hot-dip galvanized

Total width	Approx.kg	For padlock Part-No.	Price €	With triangular lock Part-No.	Price €	With Euro profile cylinder lock Part-No.	Price €
1500 mm	32.0	77-2-15-PH	€ 221,10	77-2-15-TH	€ 281,40	77-2-15-CH	€ 341,90
2000 mm	35.0	77-2-20-PH	€ 234,50	77-2-20-TH	€ 294,80	77-2-20-CH	€ 328,30
2500 mm	38.0	77-2-25-PH	€ 247,90	77-2-25-TH	€ 308,20	77-2-25-CH	€ 341,70
3000 mm	41.0	77-2-30-PH	€ 261,30	77-2-30-TH	€ 321,60	77-2-30-CH	€ 355,10
3500 mm	44.0	77-2-35-PH	€ 274,70	77-2-35-TH	€ 335,00	77-2-35-CH	€ 368,50

For casting in concrete, hot-dip galvanized and white coated with red reflecting rings

Total width	Approx.kg	For padlock Part-No.	Price €	With triangular lock Part-No.	Price €	With Euro profile cylinder lock Part-No.	Price €
1500 mm	32.0	77-2-15-P	€ 261,30	77-2-15-T	€ 321,60	77-2-15-C	€ 348,40
2000 mm	35.0	77-2-20-P	€ 274,70	77-2-20-T	€ 335,00	77-2-20-C	€ 361,80
2500 mm	38.0	77-2-25-P	€ 288,10	77-2-25-T	€ 348,40	77-2-25-C	€ 375,20
3000 mm	41.0	77-2-30-P	€ 301,50	77-2-30-T	€ 361,80	77-2-30-C	€ 388,60
3500 mm	44.0	77-2-35-P	€ 341,90	77-2-35-T	€ 375,20	77-2-35-C	€ 402,00



Swing barrier


barrier can be swiveled horizontally, with pull rope reinforcement. Locking mechanism closed or opened by pin locking in four positions (every 90°), fitted for a padlock or with triangular locking mechanism acc. to DIN 3223 or Euro profile cylinder lock.

Swiveling post: Steel tube Ø 102 mm, hot-dip galvanized and coated red
Barrier arm: Aluminium tube 100 x 50 mm, coated white with red reflecting stripes
Height: Approx. 950 mm above ground



For casting in concrete

Barrier arm length	Approx.kg	For padlock Part-No.	Price €	With triangular lock Part-No.	Price €	With Euro profile cylinder lock Part-No.	Price €
1500 mm	32.0	77-3-15-P	€ 258,00	77-3-15-T	€ 318,30	77-3-15-C	€ 241,50
2000 mm	35.0	77-3-20-P	€ 271,40	77-3-20-T	€ 331,60	77-3-20-C	€ 250,90
2500 mm	38.0	77-3-25-P	€ 284,80	77-3-25-T	€ 345,10	77-3-25-C	€ 260,30
3000 mm	41.0	77-3-30-P	€ 298,20	77-3-30-T	€ 358,50	77-3-30-C	€ 269,70
3500 mm	44.0	77-3-35-P	€ 311,60	77-3-35-T	€ 371,80	77-3-35-C	€ 279,10



Optionally available with:
Base plate for plugging down
360 x 360 x 8 mm including 4 holes Ø 21 mm for anchor bolts,
hole pitch 260 x 260 mm, for plugging down, add letter P to the part-no.

Swing barrier

barrier can be swiveled horizontally, with bracing tube and pull rope reinforcement. Locking mechanism at the swiveling post closed or opened by pin locking in 4 positions (every 90°), fitted for a padlock or with triangular locking mechanism acc. to DIN 3223 or Euro profile cylinder lock, including two supporting posts.

Swiveling post: Steel tube Ø 102 mm, hot-dip galvanized and red coated

Barrier arm: Aluminium tube 100 x 50 mm, coated white with red reflecting stripes


Supporting post: Steel tube 70 x 70 mm, hot-dip galvanized and white coated (2 piece)

Height: Approx. 950 mm above ground



For casting in concrete

Barrier arm length	Approx.kg	For padlock Part-No.	Price €	With triangular lock Part-No.	Price €	With Euro profile cylinder lock Part-No.	Price €
3000 mm	58.0	77-4-30-P	€ 338,30	77-4-30-T	€ 371,80	77-4-30-C	€ 408,70
3500 mm	61.0	77-4-35-P	€ 355,10	77-4-35-T	€ 388,60	77-4-35-C	€ 425,40
4000 mm	65.0	77-4-40-P	€ 371,80	77-4-40-T	€ 405,30	77-4-40-C	€ 442,20
4500 mm	69.0	77-4-45-P	€ 388,60	77-4-45-T	€ 422,10	77-4-45-C	€ 458,90
5000 mm	73.0	77-4-50-P	€ 405,30	77-4-50-T	€ 438,80	77-4-50-C	€ 475,70
5500 mm	78.0	77-4-55-P	€ 422,10	77-4-55-T	€ 455,60	77-4-55-C	€ 492,40
6000 mm	83.0	77-4-60-P	€ 438,90	77-4-60-T	€ 472,30	77-4-60-C	€ 509,20



Optionally available with:

Base plate for plugging down

Swiveling post base plate 360 x 360 x 8 mm, including 4 holes Ø 21 mm for anchor bolts, hole pitch 260 x 260 mm. 2 base plates for supporting post 220 x 220 x 8 mm, hole pitch 140 x 140 mm for plugging down, add letter **P** to part-no.

Recommended foundation depth: 900 mm

Access barrier

Main support: Steel construction 70 x 70 mm square tube with ground plate 360 x 360 x 8 mm for plugging down, including 4 holes Ø 20 mm for anchors, hot-dip galvanized and powder-coated red

Supporting post: Steel tube 70 x 70 mm with ground plate 220 x 220 x 8 mm including 4 holes Ø 20 mm for anchors

Barrier arm: Thick-walled Ø 80 mm aluminium tube with counterweight, uncoated with white/red reflecting stripes

Locking mechanism: At the supporting post, can be fixed by the main support pin when the arm is open

Total width: Clear width + approx. 900 mm

Height: Approx. 950 mm above ground




Clear width	Approx.kg	For padlock Part-No.	Price €	With triangular lock Part-No.	Price €	With Euro profile cylinder lock Part-No.	Price €
3000 mm	50.0	77-5-30-P	€ 375,20	77-5-30-T	€ 435,50	77-5-30-C	€ 448,90
4000 mm	70.0	77-5-40-P	€ 408,70	77-5-40-T	€ 469,00	77-5-40-C	€ 482,40
5000 mm	90.0	77-5-50-P	€ 442,20	77-5-50-T	€ 502,50	77-5-50-C	€ 515,90
6000 mm	110.0	77-5-60-P	€ 482,40	77-5-60-T	€ 542,70	77-5-60-C	€ 556,10
7000 mm	125.0	77-5-70-P	€ 529,30	77-5-70-T	€ 589,60	77-5-70-C	€ 603,00

	Approx.kg	Part-No.	Price €
Set of mounting bolts type 3, to be fixed by plugs		N570.73D	€ 00,00

Set of ground sockets with ground anchor plate for main and supporting posts, for casting in concrete, hot-dip galvanized, including bolts M16	16.0	N511.92D	€ 00,00
---	------	----------	---------

Pull rope reinforcement	N511.95D	€ 00,00
--------------------------------	----------	---------



Recommended foundation dimensions:

Main support

Width 550 x 550 mm, depth 900 mm

Supporting post

Width 400 x 400 mm, depth 900 mm

Access barrier

Main support: Steel Construction
70 x 70 mm square tube with ground plate
360 x 360 x 8 mm for plugging down,
including 4 holes Ø 20 mm for anchor,
hot-dip galvanized and powder-coated red

Barrier arm: Thick-walled Ø 80 mm aluminium tube with counterweight, uncoated with white/red reflecting stripes

Swing post: Aluminium tube with foot

Locking mechanism: At the main support with a locking pin, for fixing the arm in open or closed position


Total width: Clear width + approx. 900 mm

Height: Approx. 950 mm above ground



Clear width	Approx.kg	For padlock Part-No.	Price €	With triangular lock Part-No.	Price €	With Euro profile cylinder lock Part-No.	Price €
3000 mm	50.0	77-6-30-P	€ 381,90	77-6-30-T	€ 442,20	77-6-30-C	€ 455,60
4000 mm	70.0	77-6-40-P	€ 415,40	77-6-40-T	€ 475,70	77-6-40-C	€ 489,10
5000 mm	90.0	77-6-50-P	€ 448,90	77-6-50-T	€ 509,20	77-6-50-C	€ 522,60
6000 mm	110.0	77-6-60-P	€ 489,10	77-6-60-T	€ 549,40	77-6-60-C	€ 562,80
7000 mm	125.0	77-6-70-P	€ 536,00	77-6-70-T	€ 596,30	77-6-70-C	€ 609,70

	Approx.kg	Part-No.	Price €
Set of mounting bolts type 3, to be fixed by plugs		N570.72D	€ 00,00
Ground socket with ground anchor plate for main support, for casting in concrete, hot-dip galvanized, including bolts M16	16.0	N511.91D	€ 00,00
		N511.95D	€ 00,00
Pull rope reinforcement			



Manual barrier

with pneumatic spring and fixed pole support

Main support: Steel construction 120 x 80 mm square tube with base plate 360 x 360 x 8 mm for plugging down, including 4 holes Ø 20 mm for anchor, hot-dip galvanized and powder-coated red, barrier arm can be fixed in open and closed position

Supporting post: Steel tube 70 x 70 mm with base plate 220 x 220 x 8 mm, including 4 holes Ø 20 mm for anchor

Barrier arm: Thick-walled Ø 80 mm aluminium tube, powder-coated with red reflecting stripes

Locking mechanism at the post support

Total width: Clear width+ approx. 180 mm

Height: Approx. 950 mm above ground



Clear width	Approx.kg	For padlock Part-No.	Price €	With triangular lock Part-No.	Price €
3000 mm	45.0	77-7-30-P	€ 502,50	77-7-30-T	€ 556,00
4000 mm	48.0	77-7-40-P	€ 536,00	77-7-40-T	€ 589,60
5000 mm	51.0	77-7-50-P	€ 569,50	77-7-50-T	€ 623,10
6000 mm	54.0	77-7-60-P	€ 609,70	77-7-60-T	€ 663,30
7000 mm	58.0	77-7-70-P	€ 656,60	77-7-70-T	€ 710,20

Clear width	Approx.kg	Euro profile cylinder lock Part-No.	Price €	Triangular lock and Euro profile cylinder lock at the main support Part-No.	Price €
3000 mm	45.0	77-7-30-C	€ 393,90	77-7-30-CO	€ 629,80
4000 mm	48.0	77-7-40-C	€ 417,40	77-7-40-CO	€ 663,30
5000 mm	51.0	77-7-50-C	€ 440,80	77-7-50-CO	€ 696,80
6000 mm	54.0	77-7-60-C	€ 00,47	77-7-60-CO	€ 727,00
7000 mm	58.0	77-7-70-C	€ 501,80	77-7-70-CO	€ 783,90

	Approx. kg	Part-No.	Price €
Set of mounting bolts type 3, to be fixed by plugs		N570.73D	€ 00,00

Set of ground sockets with ground anchor plate for main and supporting posts, for casting in concrete, hot-dip galvanized, including bolts M16	16.0	N515.92D	€ 00,00
--	------	----------	---------

Pull rope reinforcement		N515.95D	€ 00,00
--------------------------------	--	----------	---------


Recommended foundation dimensions:

Main support

Width 550 x 550 mm, depth 900 mm

Supporting post

Width 400 x 400 mm, depth 900 mm





Swing barrier

barrier can be swiveled horizontally, with two supporting posts. Locking mechanism at the opened or closed barrier at the respective supporting post, fitted for a padlock, triangular locking mechanism acc. to DIN 3223 or Euro profile cylinder lock.

Swiveling post: Steel tube Ø 102 mm

Barrier arm: Steel tube 60 x 40 mm

Supporting post: Steel tube 70 x 70 mm

Height: Approx. 950 mm above ground


For casting in concrete, hot-dip galvanized



Total width	Approx.kg	For padlock Part-No.	Price €	With triangular lock Part-No.	Price €	With Euro profile cylinder lock Part-No.	Price €
2500 mm	39.0	77-9-25-PH	€ 288,10	77-9-25-TH	€ 314,90	77-9-25-CH	€ 348,40
3000 mm	43.0	77-9-30-PH	€ 304,80	77-9-30-TH	€ 331,60	77-9-30-CH	€ 365,15
3500 mm	47.0	77-9-35-PH	€ 321,60	77-9-35-TH	€ 348,40	77-9-35-CH	€ 381,90
4000 mm	49.0	77-9-40-PH	€ 338,30	77-9-40-TH	€ 365,10	77-9-40-CH	€ 398,60
4500 mm	51.0	77-9-45-PH	€ 355,10	77-9-45-TH	€ 381,90	77-9-45-CH	€ 415,40

For casting in concrete, hot-dip galvanized and red coated with white reflecting stripes

Total width	Approx.kg	For padlock Part-No.	Price €	With triangular lock Part-No.	Price €	With Euro profile cylinder lock Part-No.	Price €
2500 mm	39.0	77-9-25-P	€ 324,90	77-9-25-T	€ 358,45	77-9-25-C	€ 395,30
3000 mm	43.0	77-9-30-P	€ 341,70	77-9-30-T	€ 375,20	77-9-30-C	€ 412,10
3500 mm	47.0	77-9-35-P	€ 358,45	77-9-35-T	€ 391,90	77-9-35-C	€ 428,80
4000 mm	49.0	77-9-40-P	€ 375,20	77-9-40-T	€ 408,70	77-9-40-C	€ 445,50
4500 mm	51.0	77-9-45-P	€ 395,30	77-9-45-T	€ 428,80	77-9-45-C	€ 465,60



Base plate for plugging down

Base plate for main support 360 x 360 x 8 mm including 4 holes Ø 21 mm for anchor bolts, hole pitch 260 x 260 mm

2 base plates for supporting posts 220 x 220 x 8 mm, hole pitch 140 x 140 mm, for plugging down. Add letter **P** to part no.

Know INDIA - Valluvar Kottam is a popular monument in Chennai, Tamilnadu, India which is dedicated to the classical Tamil poet, philosopher and saint Thiruvalluvar. Thiruvalluvar wrote his famous Thirukkural





the products shown in this catalogue
designed & manufactured by NavAstrid in chennai

www.navastrid.de

Veppampattu, TamilNadu, - 602024. INDIA